

SKID STEER LOADERS **S850**



Tipping load (ISO 14397-1) Rated operating capacity (ISO 14397-1) Pump capacity Pump capacity (with high flow option) System relief at quick couplers Max. travel speed (high range) Max. travel speed (low range)

3515 kg 1850 kg 87.10 L/min 138.50 L/min 23.8-24.5 MPa 19 8 km/h 11.4 km/h

Engine

Make / Model Fuel Cooling Maximum power at 2400 RPM (SAE J1995) Torque at 1600 RPM (SAE J1995 Gross) Number of cylinders Displacement Fuel tank

Kubota / V3800-DI-T-E3 Diesel Liquid 68.6 kW 315.0 Nm 3769 cm³ 111.60 L

Weights

Operating weight Shipping weight

4540 kg 4254 kg

Manual

Lift arm support

Parking brake

Seat belt

Seat bar

Work lights, front and rear

14 x 17.5, 12-ply, Bobcat heavy duty tyres

Turbo-charger with approved spark arrestor

Warranty: 24 months or 2000 hours (whichever occurs

Controls

Vehicle steering Loader hydraulics tilt and lift Front auxiliary (standard)

Direction and speed controlled by two hand levers Selectable Joystick Control (SJC) Electrical switch on right-hand steering lever

Drive System

Transmission

Infinitely variable tandem hydrostatic piston pumps, driving two fully reversing hydrostatic motors

Standard Features

Two-speed travel

Selectable Joystick Controls (SJC) or Standard Control

Power Assist (SCPA)

High-back adjustable suspension seat Automatically activated air intake heater Auxiliary hydraulics: variable flow/maximum flow Bob-Tach™ frame

Bobcat Interlock Control System (BICS)

Deluxe operator cab 1

Electrically activated proportional front auxiliary hydraulics

Engine/hydraulics system shutdown

Roll Over Protective Structure (ROPS) – meets requirements of SAE-J1040 and ISO 3471; Falling Object Protective Structure (FOPS) - meets requirements of SAE-J1043 and ISO 3449, Level I

Options

Heavy duty radio High-Flow hydraulics Deluxe instrument panel

Deluxe pressurized cab with heating

Air conditioning Power Bob-Tach™

12 x 16.5, 12-ply, Bobcat heavy duty tyres, offset rims


14 x 17.5, 12-ply, Severe duty tyres, poly filled

14 x 17.5, Solid flex tyres Air ride seat with 3 point seat belt Back-up alarm

Beacon Engine block heater Fire extinguisher

Strobe

Dimensions



4532.0 mm	(J)	3657.0 mm
2118.0 mm	(K)	754.0 mm
27.0°	(L)	42.0°
218.0 mm	(M)	98.0°
1342.0 mm	(N)	2032.0 mm
3030.0 mm	(O)	2262.0 mm
3751.0 mm	(P)	1652.0 mm
30.0°	(Q)	2005.0 mm
2951.0 mm	,	

Attachments

(B) (C) (D)

ÌΕ)

(F)

(Ġ) (H)

Angle Brooms Auger Accessories Augers Backhoes Bale Forks Breaker Accessories **Breakers** Brushcat™ Rotary Cutters **Brush Saws** Concrete Pumps Construction / Industrial **Buckets** Dozer Blades **Drop Hammers Dumping Hoppers** Flail Cutters Forestry Cutters Graders Grapples, Industrial Landplanes Landscape Rakes

Laser Equipment

Miscellaneous

Mixing Buckets

Mowers Pallet Fork Accessories Pallet Forks, Hydraulic Planer Accessories Planers Root Grapples **Rotary Grinders** Silt Fence Installers Skeleton Buckets Snow & Light Material Buckets Snow Blades Snow Pushers Sod Layers Soil Conditioners Spreaders Steel Tracks Stump Grinders Tree Transplanters Trench Compactors **Utility Frames** Vibratory Rollers Wheel Saws Wood Chippers



Bobcat is a Doosan Company.

Doosan is a global leader in construction equipment, power & water solutions, engines, and engineering proudly serving customers and communities for more than a century. | Bobcat and the Bobcat logo are registered trademarks of Bobcat Company in the United States and various other countries. ©2019 Bobcat Company. All Rights Reserved.





