

SKID STEER LOADERS **S530**



Engine

Make / Model Compliancy Fuel Cooling Power at 2600 RPM (ISO 14396) Torque at 1800 RPM (ISO 14396) Number of cylinders Displacement Fuel tank

Bobcat 2.4L, 97/68 EC Stage V

Diesel Liquid 41.0 kW 204.0 Nm 2392 cm³ 93.70 L

Spark Arrester

Weights

Operating weight 2952 kg 2581 kg Shipping weight

Controls Vehicle steering

Loader hydraulics tilt and lift Front auxiliary (standard)

Hand Levers or optional Selectable Joystick Controls (SJC)

Foot Pedals or optional Selectable Joystick Controls (SJC) Proporcional switch on Hand Levers or optional Selectable Joystick Controls (SJC)

Drive System

Transmission

Infinitely variable tandem hydrostatic piston pumps, driving two fully reversing hydrostatic motors

Standard Features

Bobcat Interlock Control System (BICS)

Parking brake

Deluxe operator cab* Includes interior cab foam, side, top and rear windows, Deluxe wire harness, dome light and electrical power port 1

Noise reduction kit

Operating lights, front and rear Deluxe instrument panel

Keyless start with password capability

Suspension seat Seat belt Seat bar

Hydraulic bucket positioning (including ON/OFF switch) 10 x 16.5, 10-ply, Heavy duty tyres

Bob-Tach™ frame Cushioned lift and tilt cylinders Lift arm support Engine/hydraulics system shutdown Automatically activated glow plugs Electrically activated proportional front auxiliary hydraulics Auxiliary hydraulics: variable flow/maximum flow Machine IQ (telematic) Manual CF certification Warranty: 24 months or 2000 hours (whichever occurs

Roll Over Protective Structure (ROPS) – meets requirements of SAE-J1040 and ISO 3471; Falling Object Protective Structure (FOPS) - meets requirements of SAE-J1043 and ISO 3449, Level I

Options

Deluxe pressurized cab with heating Deluxe pressurized cab with HVAC Selectable Joystick Controls (SJC - R/C Ready) Cloth Suspension Seat 10 x 16.5, 10-ply, Heavy duty tyres, offset rims 10 x 16.5, 10-ply, Versatile duty tyres 10 x 16.5, 10-ply, Severe duty tyres

31 x 10 - 20, Industrial duty tyres High-flow auxiliary hydraulics

7-pin attachment control

2 Speed Power Bob-Tach™ Back-up alarm Radio Beacon Road Option

Automatic Ride Control Automatic Reversing Fan

Custom paint color (min order of 5 units)

Environmental


DOOSAN

Operator LpA(98/37 & 474-1) 86 dB(A) Noise level LWA(EU Directive 2000/14/EC) 98 dB(A) Whole body vibration (ISO 2631-1) High speed 0.86 ms⁻² Whole body vibration uncertainty 0.43 ms⁻² Hand-arm vibration (ISO 5349-1) High speed 1.31 ms⁻²

Bobcat is a Doosan Company.

Doosan is a global leader in construction equipment, power & water solutions, engines, and engineering proudly serving customers and communities for more than a century. | Bobcat and the Bobcat logo are registered trademarks of Bobcat Company in the United States and various other countries. ©2019 Bobcat Company. All Rights Reserved.

Dimensions



(A)	3901.0 mm	(J)	3023.0 mm
(B)	1972.0 mm	(K)	828.0 mm
(C)	24.2°	(L)	42.0°
(D)	185.0 mm	(M)	97.0°
(E)	1082.0 mm	(N)	1727.0 mm
(F)	2657.0 mm	(O)	2024.0 mm
(G)	3378.0 mm	(P)	1374.0 mm
(H)	30.0°	(Q)	1643.0 mm
(l)	2319.0 mm		

Attachments

Angle Brooms Auger Accessories Augers Backhoes Bale Forks Box Blades **Breaker Accessories Breakers** Brushcat™ Rotary Cutters **Brush Saws** Combination Buckets Concrete Mixers Construction / Industrial **Buckets** Diagers Dozer Blades **Drop Hammers Dumping Hoppers** Fertilizer and Grain Buckets Flail Cutters General Purpose (GP) Bucket Graders Grapples, Industrial Landplanes Landscape Rakes Laser Equipment Low Profile Buckets Miscellaneous Mixing Buckets Mowers

Pallet Fork Accessories Pallet Forks, Hydraulic Planer Accessories Planers Remote Control Root Grapples Scarifiers Scrapers Skeleton Buckets Snow & Light Material Buckets **Snow Blades** Snow Pushers Snow V-Blades Sod Layers Soil Conditioners Spreaders Steel Tracks Stump Grinders Sweepers Tillers Tilt-Tatch Tree Transplanters Trench Compactors Trenchers Utility Forks Vibratory Rollers Wheel Saws Whisker Brooms Wood Chippers

