

Small Articulated Loaders / L23 Small Articulated Loader

L23 Loader Specifications & Options

See all the L23 small articulated loader specs and compare with other models.

Standard

☒

Optional

N/A

Not Applicable

Units

METRIC

Bobcat L23

Engine

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	18.49 kW
Turbocharged Engine	N/A

Performance

Rated Operating Capacity Straight (ISO)	632.76 kg
Rated Operating Capacity Art. (ISO)	525.71 kg
ROC with Counterweight Option Straight	823.27 kg
ROC with Counterweight Option Art.	667.23 kg
Tipping Load Straight	1265 kg
Tipping Load Art.	1051 kg
Operating Weight	1719 kg
Travel Speed	13.2 km/h

Capacities

Fuel Tank	36.34 l
-----------	---------

Hydraulic System

System Relief @ Quick Couplers	2900 psi
Auxiliary Std Flow	45.8 l/min

Drive System

Drive Type	Hydrostatic pump driving 4 independent wheel motors
------------	---

Dimension

Length	3109 mm
Length without Attachment	2367 mm
Length with Standard Bucket	3109 mm
Width (over tires)	1.1 m
Width (with bucket)	1118 mm
Height with Operator Cab	1984 mm
Height to Bucket Hinge Pin Ext	2169 mm
Height to Bucket Hinge Pin Ret	2169 mm
Max Reach	426.72 mm
Turning Radius Inside	1961 mm
Turning Radius Outside	2563 mm
Wheelbase	1199 mm
Articulation Angle	43°
Dump Angle @ Maximum Height	40°
Ground Clearance	0.14 m
Rollback Angle	32°
Tire Size	23X8.5-12
Wheel Tread	0.87 m

Features

Air Conditioning	N/A
Adjustable Seat	■
Backup Alarm	■
BICS System (Interlock)	■
Cab Enclosure	☑
Cab Heater	☑
Operating Lights	☑
Rear Window	☑
Lift-Arm Support	■
Two Speed Travel	N/A
Deluxe Instrumentation	N/A
Hydraulic Bucket Positioning	■
Auxiliary Hydraulics	■
Spark Arrestor Muffler	■
Bob-Tach Attachment System	■
Horn	■
Front and Rear Work Lights	■
Rotating Flashing Beacon	☑
Turn Signals	☑
Tires-Ply Rating	10
Heavy-Duty Float Tires	☑
Cup Holder	■

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.